



# GM005 - 1/2" Oval Gear Pulse Meter



The GM005 Meter is a low to medium flow range model. The construction of this meter allows for fast and easy servicing while installed.

**ACCURACY: ± 0.5% OF READING**

### Select Your Body Material:

Aluminum  
Stainless Steel



### Features and Benefits:

- ✓ High viscosity PPS and Stainless Steel rotors available.
- ✓ Extremely accurate even with viscous fluids.
- ✓ Handles particles sizes to 0.011"/0.28 mm.
- ✓ Meter design minimizes the number of wear-able parts – extending product life.
- ✓ Comes with Read Switch as standard, Hall Effect Sensor\* optional.
- ✓ Choose from a variety of Output and Display Options.
- ✓ Certificate of Accuracy supplied with meter.

### GM005 - SPECIFICATIONS

Fitting Type:	BSP or NPT (Female)
Sensor Options:	Reed Switch / Hall Effect Sensor*
Rotor Materials:	PPS or High Viscosity PPS 316 Stainless Steel or High Viscosity Stainless Steel
O-Ring:	Viton (Standard), Teflon® (Optional)
Output Options:	Pulse Out or Local 4-20 mA Transmitter
Display Options:	Standard LC Display or Local 4-20 mA with Standard Display
Flow Range:	0.26 - 7.9 GPM (1 - 30 LPM)
Flow Range @ < 5 cps:	0.80 - 6.6 GPM (3 - 25 LPM)
Accuracy:	± 0.5% of reading
Repeatability:	± 0.03%
Maximum Viscosity:	Standard Rotors: 1,000 cps High Viscosity Rotors: 1,000,000 cps
Pressure Rating:	800 PSI / 55 BAR
Maximum Temperature:	PPS Rotors: 176°F / 80°C SS Rotors: 248°F / 120°C
Typical K-Factor:	Single Pickup: 424 PPG / 112 PPL Double Pickup: 848 PPG / 224 PPL
Wetted Mat'l. - Housing:	Aluminum: Aluminum Stainless Steel: 316 Stainless Steel
Wetted Mat'l. - Bearings:	PPS / Carbon
Wetted Mat'l. - Shaft:	316 Stainless Steel
Frequency Range:	1.8 - 55.8 Hz @ 0.26 - 7.9 GPM
Recommended Strainer Size:	60 mesh
Shipping Weight (approx.):	Aluminum: 3.25 lbs. (1.5 kg) Stainless Steel: 6.0 lbs. (2.7 kg)
Remote Display:	Option Available: Model GG500-4
Remote Transmitter:	Options Available: Model GA500 & GX500-4

\* Hall Effect Sensor requires dedicated power source.

BUY SMART . BUY VALUE . BUY